




5
YEARS
WARRANTY



på alle elektriske / mekaniske enheder



på alle reservedele

5 års garanti

Mini Splits




12/18K Btu/h

Energy Class	Wi-Fi Standard	Ionizer	Triple Action Filter	Sterilization HEPA Filter	Powerful Self-Cleaning	High Density Air Dust Filter	Ultra Silence Mode
R32 ECO Refrigerant	Follow Me	Sleep Mode	Turbo Mode	Mute Mode	Anti-Cold Air Function	Low Ambient Cooling	Golden Fin

Model			GR1VI32-12WF/ GR1VO32-12	GR1VI410-18WF/ GR1VO410-18
Cooling Capacity (Btu/h)			12.000 (1.385-15.162)	18.000 (6.260-20.880)
Cooling Capacity (kWatt)			3.52 (0.41-4.44)	5.27 (1.83-6.96)
Heating Capacity (Btu/h)			13.000 (1.228-14.866)	19.000 (4.760-23.000)
Heating Capacity (kWatt)			3.81 (0.36-4.36)	5.56 (1.39-6.74)
Seasonal Efficiency (In accordance to EN14825)	Cooling	Pdesign (kW)	3.5	5.3
		Energy Class	A++	A++
		SEER	6.1	6.6
		Annual Power Consumption (kWh/year)	206	281
	Heating (Middle Zone)	Pdesign (kW)	2.9	4.2
		Energy Class	A+	A+
		SCOP	4.0	4.0
		Annual Power Consumption (kWh/year)	1.015	1.470
	Heating (Warm Zone)	Pdesign (kW)	3.3	4.3
		Energy Class	A+++	A++
		SCOP	5.4	4.6
		Annual Power Consumption (kWh/year)	870	1.309
Voltage / Frequency / Phase (V/Hz/Ph)			220-240/50/1	220-240/50/1
Current Input (A)	Cooling		5.25 (0.57-6.2)	7.14 (0.61-10.25)
	Heating		4.87 (0.50-5.82)	6.90 (0.87-10.48)
Power Input (W)	Cooling		1.208 (131-1.426)	1.643 (140-2.345)
	Heating		1.340 (113-1.340)	1.586 (200-2.410)
Air Flow Volume (m³/h) (Max./Hi/Med/Low)			530/421/305	740/620/480
Sound Power Level (dB(A))	Indoor unit (Silent/Low/Medium/High)		21/26/30/37.5	21/33/35/42.5
	Outdoor unit		54	55
Sound Power Level (dB(A))	Indoor unit		50	54
	Outdoor unit		63	63
Compressor Type			ROTARY	ROTARY
Liquid line Gas line			1/4" 3/8"	1/4" 1/2"
Power Supply Wire Outdoor (No x mm²) / Fuses (A)			3x1.5 / 10	3x2.5 / 16
Signal Wires (No x mm²)			5x1.5	5x1.5
Dimensions WxDxH (mm)	Indoor unit		897x182x312	1.004x205x350
	Outdoor unit		770x300x555	800x333x554
Net Weight (kg)		Indoor / Outdoor	9.9/27	13.5/35.1
Refrigerant / Charge (kg)			R32 / 0.8	R410A / 1.35
Outdoor Operation Temperature Range (°C)	Cooling		-15~50	-15~50
	Heating		-15~30	-25~30





Lys sensor

Sluk lysene og nyd ideelle forhold på dit sted! Sensoren realiserer fraværet af lys og 5 " senere falder intensiteten af lysstyrken på dit klimaanlæg.

Samtidig sænkes blæserhastigheden, og lydstyrken er deaktiveret.

GRANDE



*Since 1966**

INVENTORDANMARK APS
PLANTAGEVEJ 35
8250 EGÅ

WWW.INVENTORDANMARK.DK